

HOSE 2 GO H2GO

Constant pressure water supply unit without a battery or pump

THE HOSE 2 GO provides a consistent flow of water that allows for both cooling and dust suppression when cutting, core drilling and grinding concrete. Once the user has filled the unit from a tap it's ready to go, giving the user up to 30 minutes of constant flowing water without using a battery or pump.

CHALLENGE ON THE JOB?

- Getting a constant flow of water for dust suppression
- Tanks being too heavy to move around
- Tanks breaking down
- Running out of battery power
- Limited availability of on site water supply

SPECIFICATIONS

 Length
 325mm/12.8in

 Width
 144mm/5.7in

 Height (placed horizontally)
 800mm/31.5in

 Weight (Dry)
 5.7kg/12.6 lb

 Weight (Full)
 19.5kg/43 lb

 Full tank capacity
 13.8L/3.65 gal

SOLUTIONS

- No pump which means greater reliability
- No complicated electrics to breakdown
- No need to manually pump for water pressure you need
- ✓ On the job dust suppression easy and simple
- Up to 30 mins constant flow of water
- Portable only weighs 20kg (44lb) so you can use it anywhere
- On the job cooling ensuring longer blade life







of water

13.8 (3.6 gal) litre capacity

Usage up to

30 mins

Cutting, washing or drilling, the Hose 2 Go provides a water supply without the need to manually pump to maintain pressure.





Carry the Hose 2 Go to job site with the strap attachment

